



■ SPECIFICATIONS

Voltage rating: 250V AC, DC
 Current rating: 7A, AC, DC
 Withstanding Voltage: 1500V AC/minute
 Insulation resistance: 1000M Ω min
 Temperature range: -25°C~+85°C
 Contact resistance: 10m Ω max

■ WAFER

Poles : 02-24
 Pin Material: Brass /Tin-plated

EAST-XXX 02 X 01 XX X X

No. of Pins

004 -> 4P
 008 -> 8P
 024 -> 24P

Environment Protection:

R for RoHS
 G for GP
 H for Halogen-free

Packing:

C-Tray, D-Pe bag, E-Box

Plating:

A- Flash Gold in contact area/
 80u" Min Tin in solder area.

I- Tin Plated

Color:

Ax:Red, Bx:Orange, Cx:Yellow
 Dx:Green, Fx:Blue, Gx:Purple,
 Kx:Black, Lx:White,
 Jx:Transparent color

TOLERANCE		TITLE:	
LINEAR	ANGLES	4.20mm Pitch ATX 90D Vertical DIP type	
X.±0.50	X'.±2.0'	PART NO.: SEE TABLE	
.X±0.38	.X'±1.0'	DWG NO.: EAST-XXX03-01	
.XX±0.25	.XX'±	UNITS	SCALE
.XXX±0.15	.XXX'±	MM	1:1
APPD:		DRWN: Rocky	
CHKD:		DATE: 2014-3-28	
深圳市东方御业科技有限公司 Tel:0755-27155560 https://dfyyconn.1688.com		SHEET	REV
		1 OF 1	A/0